



High Output Version



Eco Version

Audible Signals - Industrial ECO TLM AUDIBLE MODULES



Tel +31(0)85-27 36 750
Fax +31(0)85-27 36 760
Web www.inrato.com

Industrial LED-TLM Eco Tower Light > Audible Modules

Product overview

These audible modules have been designed for use in conjunction with the Moflash LED-TLM Eco Tower Light Module range. They are a simple fix addition that offers an audible warning signal in addition to the multiple visual ones that the tower offers.

The module can be pre-set with either a pulsed or continuous tone. The Eco buzzers have been designed for local indication only but a higher decibel output version (Ac only) is available.

This has two dB outputs selectable by a slide switch inside the enclosure.

Features



- Continuously rated
- Low current consumption
- Cost effective audible solution
- Quick & easy installation or upgrade

Material

Black ABS Plastic



ECO TLM-AUD-02 >

Code No: LED-TLM-AUD-02
Voltage: 24v Dc ---
Operating Temperature: -25 to +55 °C
Current: 55mA
Pulsed Tone Rate: 60/80 (time/min)
Output dB: 100
IP Protection: IP65






ECO TLM-AUD-04 >

Code No: LED-TLM-AUD-04
Voltage: 85-275v Ac ~
Operating Temperature: -25 to +55 °C
Current: <55mA
Output dB: 80
IP Protection: IP54



HIGH OUTPUT TLM-AUD120-04 >

Code No: LED-TLM-AUD120-04
Voltage: 85-275v Ac ~
Operating Temperature: -25 to +55 °C
Current: <20
Output dB: 100-120 selectable
IP Protection: IP65



APPROVALS and
CONFORMITIES

